



## PG & METRIC BLIND STOPS

Technical Details:

Material

Hexagonal locknut: Polyamide PA6 V2 + 30% GF

Connection thread: Metric (EN 60423) , PG (DIN40430)

Temperature Range: -30 °C +80 °C

+150 °C (short term)

Properties

For tightening of cable glands

UV resistance

Halogen Free



AG Thread	Grey Code	L. Grey Code	Black Code	H mm	mm
M 12 x 1,5	MSG 01	MSL 01	MSB 01	5	18
M 16 x 1,5	MSG 01	MSL 01	MSB 01	5	22
M 20 x 1,5	MSG 01	MSL 01	MSB 01	6	26
M 25 x 1,5	MSG 01	MSL 01	MSB 01	6	32
M 32 x 1,5	MSG 01	MSL 01	MSB 01	7	41
M 40 x 1,5	MSG 01	MSL 01	MSB 01	7	50
M 50 x 1,5	MSG 01	MSL 01	MSB 01	8	60
M 63 x 1,5	MSG 01	MSL 01	MSB 01	8	75
PG7	OSG 01	OSL 01	OSB 01	5	19
PG9	OSG 02A	OSL 02A	OSB 02A	5	19
PG11	OSG 01	OSL 01	OSB 01	5	22
PG 13,5	OSG 01	OSL 01	OSB 01	5	24
PG 16	OSG 01	OSL 01	OSB 01	6	27
PG 21	OSG 01	OSL 01	OSB 01	6	30
PG 21	OSG 01	OSL 01	OSB 01	7	36
PG 21	OSG 01	OSL 01	OSB 01	7	46
PG 21	OSG 01	OSL 01	OSB 01	8	60
PG 21	OSG 01	OSL 01	OSB 01	8	65
PG 21	OSG 01	OSL 01	OSB 01	8	70