

TM
TM 208/12 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

Delivery status	This article will no longer be available in the future.
Available until	2018-04-30
Type	TM 208/12 V0
Order No.	1806220000
Version	TM, Sleeve x 30 mm, PVC, Colour: Transparent, Conductor O.D.: 30 - 35 mm
GTIN (EAN)	4032248275731
Qty.	50 pc(s).
Alternative product	1866680000

Data sheet

TM
TM 208/12 V0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	30 mm	Width (inches)	1.181 inch
Height	12 mm	Height (inches)	0.472 inch
Depth	30 mm	Depth (inches)	1.181 inch
Net weight	2.8 g		

General data

Colour	Transparent	Material	PVC
Operating temperature range	-40...80 °C	Recommended industries	Transportation, Machinery
Type of printing	blank	UL 94 flammability rating	V-0
Width	30 mm		

Conductor and cable markers

Conductor O.D.	30 - 35 mm	Conductor O.D., max.	35 mm
Conductor O.D., min.	30 mm	Conductor cross-section, max.	300 mm ²
Conductor cross-section, min.	240 mm ²		

Classifications

ETIM 3.0	EC001530	ETIM 4.0	EC001288
ETIM 5.0	EC001288	ETIM 6.0	EC001530
UNSPSC	44-12-17-08	eClass 5.1	27-14-91-03
eClass 6.2	27-14-91-29	eClass 7.1	27-14-91-29
eClass 8.1	27-14-91-03	eClass 9.0	27-14-07-08
eClass 9.1	27-40-04-01		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD, Zuken E3.S
------------------	--