

**TM**  
**TM 209/20 V0**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

**General ordering data**

Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2018-04-30
Type	TM 209/20 V0
Order No.	<a href="#">1806410000</a>
Version	TM, Sleeve x 33 mm, PVC, Colour: Transparent, Conductor O.D.: 35 - 40 mm
GTIN (EAN)	4032248275922
Qty.	50 pc(s).
Alternative product	<a href="#">1866680000</a>

**TM**  
**TM 209/20 V0**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Width	33 mm	Width (inches)	1.299 inch
Height	20 mm	Height (inches)	0.787 inch
Depth	33 mm	Depth (inches)	1.299 inch
Net weight	4.2 g		

**General data**

Colour	Transparent	Material	PVC
Operating temperature range	-40...80 °C	Recommended industries	Transportation, Machinery
Type of printing	blank	UL 94 flammability rating	V-0
Width	33 mm		

**Conductor and cable markers**

Conductor O.D.	35 - 40 mm	Conductor O.D., max.	40 mm
Conductor O.D., min.	35 mm	Conductor cross-section, max.	500 mm <sup>2</sup>
Conductor cross-section, min.	300 mm <sup>2</sup>		

**Classifications**

ETIM 3.0	EC001530	ETIM 4.0	EC001288
ETIM 5.0	EC001288	ETIM 6.0	EC001530
UNSPSC	44-12-17-08	eClass 5.1	27-14-91-03
eClass 6.2	27-14-91-29	eClass 7.1	27-14-91-29
eClass 8.1	27-14-91-03	eClass 9.0	27-14-07-08
eClass 9.1	27-40-04-01		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
------------------	--