





- Daily program
- Slim format 17,5 mm
- Captive setting keys
- Manual override switch
- Permanently ON / AUTO

### Highlights

- Easy programming with captive setting keys
- Easy to read switching program
- Manual override switch Permanently ON / AUTO
- Simple to install



### VS 10/14



## Time Switches VS 10/14 for DIN-rail mounting

Technical data	
<b>Voltages</b>	230 V, 50–60 Hz
<b>Power consumption</b>	approx. 1 VA
<b>Switch (potential-free)</b>	Normally open, gap < 3 mm ( $\mu$ )
<b>Contact material</b>	AgCdO
<b>Switching capacity</b>	16 A / 250 V $\sim$ at $\cos\phi=1$ 1.5 A with inductive load max. filament lamp load 2000 W
<b>Minimum switching interval</b>	15 min
<b>Time base</b>	Quartz
<b>Power back-up (at 20°C)</b>	$\cong$ 70 h
<b>Accuracy (at 20°C)</b>	$\cong \pm 1.5$ sec/day
<b>Permitted ambient temperature</b>	-5°...+50°C
<b>Enclosure</b>	self-extinguishing thermoplast
<b>Dimensions</b>	45 x 17.5 x 58 mm
<b>DIN-rail mounting</b>	35 mm section rail (DIN EN 50022)
<b>Type of connection</b>	Screw terminals
<b>Type of protection</b>	IP 20 to DIN EN 60529
<b>Class of protection</b>	II when installed according to regulations

Rights to technical amendments reserved.

Type/Order No.	Version
<b>VS 10.18</b>	Day without reserve
<b>VS 14.18</b>	Day with reserve