

FEATURES: FC-35 ELECTRIC MEASURING TONGS COMPACT

- rubberized shock-resistant housing protects the device from various mechanical damage
- Shockproof protected design allows the device to operate in harsh environments
- Ergonomic and modern design has stand-emphasis for convenient vertical position
- intended for use both indoors and outdoors
- LCD Backlight
- Auto power off

SCOPE: FC-35 PLIERS ELECTRICITY COMPACT

- Housing in everyday life;
- Service and diagnostics of power equipment;
- electronics and diagnostics of electrical appliances

Properties FC-35:

Measurement current: alternating
Disclosure coverage of 18 mm
non-contact voltage detector and flashlight
indications DATA HOLD Hold
Determination of maximum values MAX
Auto Power
Low Battery Indication
Backlight

Specifications on the current clamp FC-35 :

functions	Range	Error	FC-35
Change. A	200A	± (2.5% + 8d)	*
Constantly. V	600V	± (0.5% + 1 d)	0.2-600V auto
Change. V	600V	± (1.5% + 2 d)	0.2-600V auto
Soprotivletie	20MΩ	± (3.0% + 5 d)	0.2k-20MΩ auto
diode test	Open circuit voltage 1.5V, Test current 0.3mA (FC-35 only)		
continuity	Buzzer sounds at 100Ω		
Non-contact voltage detector: 100 – 600VAC			
Size (HxWxD)	178mm x 65mm x 32mm		
The weight	170g		

