

Connector AM-TOP®

Part no. 5




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

Ampere	16 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Weight	222 g
Declaration of Conformity	DE,VDE, AT,ÖVE, CN,CQC

Drawing



Poles	3	4	5	3	4	5
а	162	165	167	209	209	208
b	60	68	76	82	82	89
h	83	92	98	100	100	108
у	14.5	16	16	22	22	22
Terminal for cond. cross		1	1	2.5	2.5	2.5
section (mm²) minmax.		— 2.5	—2.5	—6	— 6	— 6
	a b h y	 a 162 b 60 h 83 y 14.5 	a 162 165 b 60 68 h 83 92 y 14.5 16	a 162 165 167 b 60 68 76 h 83 92 98 y 14.5 16 16 l. cross 1 1 1	a 162 165 167 209 b 60 68 76 82 h 83 92 98 100 y 14.5 16 16 22 l. cross 1 1 1 2.5	a 162 165 167 209 209 b 60 68 76 82 82 h 83 92 98 100 100 y 14.5 16 16 22 22 L cross 1 1 1 2.5 2.5