

Connector AM-TOP®

Part no. 540




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 67
Weight	191 g
Declaration of Conformity	DE,VDE, CN,CQC

Drawing



Poles	3	4	5	3	4	5
а	146	166	172	212	212	213
b	72	79	89	96	96	102
h	80	88	95	98	98	105
у	14.5	16	16	22	22	22
Terminal for cond. cross		1	1	2.5	2.5	2.5
section (mm²) minmax.		— 2.5	—2.5	—6	—6	6
	Poles a b h y	Poles 3 a 146 b 72 h 80 y 14.5 d. cross 1	Poles 3 4 a 146 166 b 72 79 h 80 88 y 14.5 16 d. cross 1 1	Poles 3 4 5 a 146 166 172 b 72 79 89 h 80 88 95 y 14.5 16 16 d. cross 1 1 1	Poles 3 4 5 3 a 146 166 172 212 b 72 79 89 96 h 80 88 95 98 y 14.5 16 16 22 d. cross 1 1 1 2.5	Poles 3 4 5 3 4 a 146 166 172 212 212 b 72 79 89 96 96 h 80 88 95 98 98 y 14.5 16 16 22 22 d. cross 1 1 1 2.5 2.5