

**Screwdriver
SDS 0.8X4.5X125**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com



Slotted screwdriver with rounded blade SD DIN 5265,
ISO 2380/2, output to DIN 5264, ISO 2380/1.
ChromTop tip, SoftFinish grip

General ordering data

| | |
|------------|---|
| Type | SDS 0.8X4.5X125 |
| Order No. | 9009020000 |
| Version | Screwdriver, Blade width (B): 4.5 mm, Blade length: 125 mm, Blade thickness (A): 0.8 mm |
| GTIN (EAN) | 4032248266883 |
| Qty. | 1 pc(s). |

Data sheet

**Screwdriver
SDS 0.8X4.5X125**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|--------|-----------------|------------|
| Length | 248 mm | Length (inches) | 9.764 inch |
| Weight | 65 g | Net weight | 60.6 g |

Screwing tools

| | | | |
|--------------|---------|---------------------|--------|
| Blade length | 125 mm | Blade thickness (A) | 0.8 mm |
| Blade type | A | Blade width (B) | 4.5 mm |
| Form | Slotted | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001395 | ETIM 4.0 | EC000158 |
| ETIM 5.0 | EC000158 | ETIM 6.0 | EC000158 |
| UNSPSC | 27-11-17-01 | eClass 5.1 | 21-04-04-01 |
| eClass 6.2 | 21-04-04-01 | eClass 7.1 | 21-04-04-90 |
| eClass 8.1 | 21-04-04-90 | eClass 9.0 | 21-04-04-07 |

Approvals

Approvals



Downloads

Approval/Certificate/Document of
 Conformity

[Declaration of the Manufacturer](#)

Data sheet

**Screwdriver
SDS 0.8X4.5X125**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Drawings

