

# mini Pro Push-In Wire Connectors

- Polycarbonate, UL 94V-0 flame-retardant shell rated at T85 (IEC).
- Spring force connector constructed from copper plate and stainless spring steel.
- Plastic shell is permanently welded together.
- Compact size design is perfect for tight spaces.
- Color-coded clear shell offers visual verification of connection.
- Recommend reusing with a wire at least one size larger than the wire previously removed.
- IEC/EN 60998 Certified and UL 486C Listed.



## PC21\* SERIES

### Electrical Ratings & Wire Range

24A, 450V, T85°C  
0,5-2,5 mm<sup>2</sup>, Rigid

### Approvals



### Dimensions (mm)

### Cat. No.

### Color

### Poles

### Packing



**PC212**

Red  
+  
Clear

2

Box of 100

Carton of 10,000  
(10 bags, 1,000 ea.)




**PC213**

Orange  
+  
Clear

3

Box of 100

Carton of 10,000  
(10 bags, 1,000 ea.)



**PC214**

Yellow  
+  
Clear

4

Box of 100

Carton of 5,000  
(10 bags, 500 ea.)




**PC215**

Grey  
+  
Clear

5

Box of 100

Carton of 5,000  
(10 bags, 500 ea.)



**PC216**

Purple  
+  
Clear

6

Box of 100

Carton of 5,000  
(10 bags, 500 ea.)