



The phase rotation indicator is a handheld instrument designed to detect the rotary field of three-phase systems.



DT-901 Phase Rotation Indicator

Environmental Specifications

Operating Temperature	0°C to +40°C
operating remperature	
Pollution Degree	2
· onution 2 cg. cc	
Type of protection	IP 40
Mechanical Specifications	
Size (H x W x D)	130mm x 69mm x 32mm
SIZC (ITX VV X D)	150111117, 05111117, 52111111
Weight	130g
vvc.g	9

Safety Specifications

Electrical Safety IEC 61010/EN61010 IEC 61557-7/EN 61557-7 Maximum Operating Voltage (Ume) 690 V Protection Levels CAT III, 600V to ground

Electrical Specifications

Power Supply – Self Powered Determine Rotary Field Direction Nominal Voltage 40 to 690 VAC Frequency Range (fn) 15 to 400HZ Current pickup 1 mA Nominal Test current (in per phase) 1 mA

Accessories

Instruction Manual, Carrying Case, Test Certificate.



Contact :

CEM INSTRUMENTS (INDIA) PVT. LTD.

32A, Ganesh Chandra Avenue, 4th Floor, Kolkata-700013 Tel: 033-22151376, 22159759

Email: info@cem-instrumets.in / info@cem-india.com Web: www.cem-instruments.in / www.cem-india.com

CEM INSTRUMENTS HEADQUATER & FACTORY

19th Building, 5th Region, Baiwangxin Industry Park, Songbai Road, Baimang, Xili, Nanshan, Shenzhen, China, 518108

Tel: +86-755-27353188, Fax: +86-755-27653699