

2. ELECTRICAL SPECIFICATIONS

Accuracy is calculated as $\pm [\% \text{ readings} + (\text{no. of digits}) \times \text{resolution}]$ at $23^\circ\text{C} \pm 5^\circ\text{C}$, relative humidity $<80\%RH$

DC Voltage

Range (V)	Resolution (V)	Accuracy
3 ÷ 1500	1	$\pm (1.0\%rdg + 2dgt)$

AC TRMS Voltage

Range (V)	Resolution (V)	Accuracy
3 ÷ 1000	1	$\pm (1.0\%rdg + 3dgt)$

Frequency range: $42.5 \div 69\text{Hz}$; Voltage zeroed for measured values $<3V$

Insulation Resistance (M Ω) – DUAL Mode

Test voltage DC [V]	Range [M Ω]	Resolution [M Ω]	Accuracy (*)
250, 500, 1000, 1500	0.1 ÷ 0.99	0.01	$\pm(5\%rdg + 5dgt)$
	1.0 ÷ 19.9	0.1	
	20 ÷ 100	1	

(*) Accuracy indicated for $VPN \geq 240V$, $R_{fault} \geq 10M\Omega$. Accuracy of R_p and $R(+)$ not declared if $R(+)$ $\geq 0.2M\Omega$ and $R(-)$ $<0.2M\Omega$

Accuracy of R_p and $R(-)$ not declared if $R(+)$ $<0.2M\Omega$ and $R(-)$ $\geq 0.2M\Omega$

Open voltage $<1.25 \times$ nominal test voltage

Short circuit current $<15\text{mA}$ (peak) for each test voltage

Nominal measured current $>1\text{mA}$ on $R = 1k\Omega \times V_{nom}$ (with VPN , VPE , $VNE = 0$)

Insulation Resistance (M Ω) –TIMER Mode

Test voltage DC [V]	Range [M Ω]	Resolution [M Ω]	Accuracy
250, 500, 1000, 1500	0.01 ÷ 9.99	0.01	$\pm(5.0\%rdg + 5dgt)$
	10.0 ÷ 99.9	0.1	

Open voltage $<1.25 \times$ nominal test voltage

Short circuit current $<15\text{mA}$ (peak) for each test voltage

Nominal measured current $>1\text{mA}$ on $R = 1k\Omega \times V_{nom}$ (with VPN , VPE , $VNE = 0$)

Setting timer: $3s \div 999s$

Continuity of protection conductors (RPE)

Range [Ω]	Resolution [Ω]	Accuracy
0.00 ÷ 9.99	0.01	$\pm(2\%rdg + 2dgt)$
10.0 ÷ 99.9	0.1	
100 ÷ 1999	1	

Test current: $>200\text{mA}$ DC up to 5Ω (included cables), Resolution 1mA , Accuracy $\pm(5.0\%rdg + 5dgt)$

Open voltage $4 < V_0 < 10V$

GFL (Ground Fault Locator) function

Test voltage DC [V]	Range [M Ω]	Resolution [M Ω]	Accuracy (*)	Position accuracy
250, 500, 1000, 1500	0.1 ÷ 0.99	0.01	$\pm(5\%rdg + 5dgt)$	$\pm 1\text{module}$
	1.0 ÷ 19.9	0.1		
	20 ÷ 100	1		

(*) Accuracy indicated for $VPN \geq 240V$, $R_{fault} \geq 10M\Omega$. Accuracy of R_p and $R(+)$ not declared if $R(+)$ $\geq 0.2M\Omega$ and $R(-)$ $<0.2M\Omega$

Accuracy of R_p and $R(-)$ not declared if $R(+)$ $<0.2M\Omega$ and $R(-)$ $\geq 0.2M\Omega$

Open voltage $<1.25 \times$ nominal test voltage

Short circuit current $<15\text{mA}$ (peak) for each test voltage

Nominal measured current $>1\text{mA}$ on $R = 1k\Omega \times V_{nom}$ (with VPN , VPE , $VNE = 0$)

The GFL function allows obtaining correct results with the following conditions:

- Test carried out with $V_{test} \geq V_{nom}$ on a single string disconnected from the inverter, from possible arresters and from earth connections
- Test performed upstream of any blocking diodes
- Single fault of low insulation located at any position in the string
- Insulation resistance of the single fault $<0.1M\Omega$
- Environmental conditions similar to those in which the fault was reported



2. GENERAL SPECIFICATIONS

DISPLAY AND MEMORY:

Features: graphic COG 128x128pxl with backlight
Memory: max 999 test

POWER SUPPLY:

Battery type: 6x1.5V alkaline batteries type AA LR06 or
6x1.1V rechargeable batteries type AA LR06
Battery life: approx. 500 tests (for each functions)
Auto Power OFF: after 5 minutes of idleness

OUTPUT INTERFACE

PC communication port: optical/USB

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H): 235 x 165 x 75mm
Weight (batteries included): 1.2kg
Mechanical protection: IP40

ENVIRONMENTAL CONDITIONS:

Reference temperature: 23°C ± 5°C
Working temperature: 0°C ÷ 40°C
Working humidity: <80%RH
Storage temperature: -10°C ÷ 60°C
Storage humidity: <80%RH
Max height of use: 2000m

REFERENCE GUIDELINES:

Instrument's safety: IEC/EN61010-1, IEC/EN61010-2-030
IEC/EN61010-2-033, IEC/EN61010-2-034
EMC: IEC/EN61326-1
Safety of measurement accessories: IEC/EN61010-031
General: IEC/EN62446
Measurement MΩ: IEC/EN 61557-2
Measurement RPE: IEC/EN 61557-4
Insulation: double insulation
Pollution degree: 2
Overvoltage category: CAT III 1500V DC, CAT III 1000V AC
Max 1500V DC, 1000VAC between inputs

This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD) and EMC 2014/30/EU

This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive