

**Accessories**  
**TS 32X15 2M/ST/ZN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com

**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

**General ordering data**

|            |                                                                                 |
|------------|---------------------------------------------------------------------------------|
| Type       | TS 32X15 2M/ST/ZN                                                               |
| Order No.  | <a href="#">0122800000</a>                                                      |
| Version    | Mounting rail, TS 32, without slot, Steel, galvanized, chromium-plated, 2000 mm |
| GTIN (EAN) | 4008190066307                                                                   |
| Qty.       | 2 m                                                                             |

## Accessories

### TS 32X15 2M/ST/ZN

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Length     | 2,000 mm | Length (inches) | 78.74 inch |
| Width      | 32 mm    | Width (inches)  | 1.26 inch  |
| Height     | 33 mm    | Height (inches) | 1.299 inch |
| Depth      | 15 mm    | Depth (inches)  | 0.591 inch |
| Net weight | 720 g    |                 |            |

### Material data

|          |        |                |                             |
|----------|--------|----------------|-----------------------------|
| Material | Steel  | Surface finish | galvanized, chromium-plated |
| Colour   | Silver |                |                             |

### System specifications

|         |              |               |       |
|---------|--------------|---------------|-------|
| Version | without slot | Mounting rail | TS 32 |
|---------|--------------|---------------|-------|

### Additional technical data

|                     |                 |                  |         |
|---------------------|-----------------|------------------|---------|
| Installation advice | Direct mounting | Type of mounting | Screwed |
|---------------------|-----------------|------------------|---------|

### Mounting rail

|                                                 |                    |           |        |
|-------------------------------------------------|--------------------|-----------|--------|
| Short circuit strength corresponds to E-Cu wire | 35 mm <sup>2</sup> | Thickness | 1.5 mm |
|-------------------------------------------------|--------------------|-----------|--------|

### Rating data

|           |              |
|-----------|--------------|
| Standards | DIN EN 60715 |
|-----------|--------------|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC001285    | ETIM 4.0   | EC001285    |
| ETIM 5.0   | EC001285    | ETIM 6.0   | EC001285    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-06-04 |
| eClass 6.2 | 27-14-11-43 | eClass 7.1 | 27-14-11-43 |
| eClass 8.1 | 27-14-11-43 | eClass 9.0 | 27-14-11-43 |
| eClass 9.1 | 27-40-06-02 |            |             |

### Product information

|                                |                                                                          |
|--------------------------------|--------------------------------------------------------------------------|
| Descriptive text ordering data | TS 32X15 2M/AL/BK: max. permitted rated current for PEN function = 192 A |
|--------------------------------|--------------------------------------------------------------------------|

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                            |
|--------------------|------------------------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>                        |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                   |
| Engineering Data   | <a href="#">0122800000_06081_TS_32X15_2M-ST-ZN_STP.stp</a> |