

**SlimFix**  
**SF 5/12 MC NE WS V2****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm<sup>2</sup>
- Markers in proven MultiCard format

**General ordering data**

|                    |                                                                        |
|--------------------|------------------------------------------------------------------------|
| Type               | SF 5/12 MC NE WS V2                                                    |
| Order No.          | <a href="#">1919650000</a>                                             |
| Version            | SlimFix, Conductor and cable markers, 4.7 - 7.4 mm, 12 x 7.4 mm, White |
| GTIN (EAN)         | 4032248556076                                                          |
| Qty.               | 160 pc(s).                                                             |
| compatible printer | <a href="#">1324380000</a>                                             |

**SlimFix**  
**SF 5/12 MC NE WS V2**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 7.4 mm  | Width (inches)  | 0.291 inch |
| Height     | 12 mm   | Height (inches) | 0.472 inch |
| Depth      | 8 mm    | Depth (inches)  | 0.315 inch |
| Net weight | 0.794 g |                 |            |

**General data**

|                                              |                           |                             |              |
|----------------------------------------------|---------------------------|-----------------------------|--------------|
| Colour                                       | White                     | Material                    | Polyamide 66 |
| Material colour according to resistance code | 9                         | Operating temperature range | -40...100 °C |
| Recommended industries                       | Transportation, Machinery | Size of labelling field     | 12x7.4 mm    |
| Type of printing                             | blank                     | UL 94 flammability rating   | V-2          |
| Width                                        | 7.4 mm                    |                             |              |

**Conductor and cable markers**

|                               |                   |                               |                    |
|-------------------------------|-------------------|-------------------------------|--------------------|
| Conductor O.D.                | 4.7 - 7.4 mm      | Conductor O.D., max.          | 7.4 mm             |
| Conductor O.D., min.          | 4.7 mm            | Conductor cross-section, max. | 10 mm <sup>2</sup> |
| Conductor cross-section, min. | 6 mm <sup>2</sup> | Halogen                       | No                 |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC001530    | ETIM 4.0   | EC001530    |
| ETIM 5.0   | EC001530    | ETIM 6.0   | EC001530    |
| UNSPSC     | 44-12-17-08 | eClass 5.1 | 27-14-91-03 |
| eClass 6.2 | 27-40-04-01 | eClass 7.1 | 27-14-91-03 |
| eClass 8.1 | 27-14-91-03 | eClass 9.0 | 27-14-07-08 |
| eClass 9.1 | 27-40-04-01 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                                                |
|------------------|------------------------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>       |
| Software         | <a href="#">M-Print PRO configuration file</a> |

### **SlimFix SF 5/12 MC NE WS V2**

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

